



C2C Marketing Inc.  
459 Bidwell Place, Victoria, BC V9C 2E5  
Ph: 250/391-9800 Fax: 250/391-9801  
Email: info@NaturesUltimate.com  
Website: www.NaturesUltimate.com

## MATERIAL SAFETY DATA SHEET

August 06

### I. PRODUCT IDENTIFICATION

**Product Name:** Natures Ultimate Orange  
**Chemical Name:** Trade Secret  
**Chemical Family:** N/A  
**Formula:** N/A  
**Molecular Weight:** N/A  
**Synonyms:** None

**Caution:** The user should conduct his/her own experiments and establish proper procedures and control before attempting use on critical parts.

### II. EMERGENCY CONTACT

**ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS**

(250) 391-9800 / (403) 255-1661 / (250) 478-4723 / (250) 209-0446 / (250) 514-2650 / (403) 554-2333

### III. PHYSICAL DATA (Determined on Typical Data)

**Boiling Point:** 310 °F to 332 °F  
**Specific Gravity:** 0.858 to 0.863  
**Vapor Pressure:** (20 °C) 3mmHg  
**Percent volatile by Volume:** 60 to 95%  
**Solubility in Water:** Emulsifies  
**Physical Description:** Clear white to yellow liquid with citrus odor  
**Evaporation Rate:** Medium to Fast

### IV. INGREDIENTS

<u>Chemical Name</u>	<u>CAS No.</u>	<u>% Weight</u>	<u>Exposure Limit</u>
Citrus Terpenes	68647-72-3	60 to 97	N/E
Proprietary ingredients	Trade Secret	3 to 40	N/E

Note: - All components are from plant based sources.  
- Major components are rated GRAS by USFDA  
- Readily biodegradable

# MATERIAL SAFETY DATA SHEET (Cont.)

Natures Ultimate Orange

---

## V. FIRE AND EXPLOSION HAZARD DATA

---

<b>Flash Point:</b>	126 °F
<b>Flammable Limits:</b>	LEL approx. 0.7% UEL Approx. 6.1%
<b>Extinguishing Media:</b>	Carbon Dioxide, Foam or Dry Chemical
<b>Special Fire Fighting Procedures:</b>	SCBA recommended, smother to exclude air, DO NOT use water, handle as an oil fire.
<b>Unusual Fire Fighting Hazards:</b>	Combustible liquid, keep away from heat, sparks, and open flames; guard against spontaneous combustion.
<b>Incompatibility (Material to avoid):</b>	Strong oxidizing agents and acidic agents including acidic clays, peroxides, halogens, vinyl chloride, and iodine pentafluoride.
<b>Hazardous Decomposition Materials:</b>	Smoke may be acrid and fume irritating, burning generates carbon monoxide, carbon dioxide, and smoke.
<b>Hazardous Polymerization:</b>	None Described
<b>Stability Considerations:</b>	Stable
<b>Conditions to Avoid for Stability:</b>	Avoid temperatures over 115 °F

---

## VI. HEALTH HAZARD DATA

---

**Effects of Over Exposure:** Product is harmful if swallowed, ingestion may cause vomiting, headache, and other medical problems; may be irritating to skin and eyes. Skin contact may cause slight redness. Contains a possible skin sensitizer, eye contact can cause moderate to high irritation. Inhalation can cause nose, throat, and respiratory tract irritation, coughing, headache. Prolonged or repeated exposure can cause drying, defatting, and dermatitis of skin.

**Signs and Symptoms of Over Exposure:** Product may be irritating to the skin, eyes, nose, and throat.

**Medical Conditions Generally aggravated by exposure:** Persons with allergies or pre-existing conditions should avoid contact with this product.

### Emergency & First Aid Procedures:

**Eyes:** Remove contact lenses at once. Flush with water for at least 15 minutes. If irritation persists seek medical attention.

**Skin:** Wash affected area with copious amounts of soap and water. If irritation develops, seek medical attention.

**Ingestion:** Seek medical attention immediately. DO NOT induce vomiting. Rinse mouth with water, then drink one glass of water. DO NOT leave victim unattended. Never give anything by mouth if victim is unconscious, is rapidly losing consciousness, or is convulsing.

**Inhalation:** If symptoms of overexposure are experienced, evacuate to fresh air. If symptoms persist, seek medical attention.

---

## VII. SPILL OR LEAK PROCEDURES

---

Mop up or otherwise absorb, move leaking containers to well-ventilated area or transfer into a secure container. No smoking. Eliminate any source of ignition, minimize inhalation. Use NIOSH approved respiratory protection device, CAUTION slippery on floor.

